

ECU100 Series

Slide-in Mounting

100M/Gigabit Industrial Media Converter Unmanaged Daughter Card

- Support up to 1 100M copper port, 1 100M fiber port, 2 Gigabit copper ports or 2 Gigabit fiber ports
- Input voltage 5VDC
- Support -40~75°C wide operating temperature range



Industrial Grade

Introduction


ECU100 series are 100M/Gigabit industrial fiber converter unmanaged daughter cards. The series include five types of products and provide 100M copper port, 100M fiber port, Gigabit copper port, Gigabit fiber port and Gigabit SFP slot. It adopts slide-in mounting. And the daughter card could be used with the media converter management card, media converter rack, media converter.

The DIP switch could implement flow control. The 1 copper port + 1 fiber port products support LFP. When the LFP function is turned on and the port has link failures, the LFP indicator would be on to send alert, offering quick troubleshooting on the scene. Hardware adopts low power consumption, wide temperature and voltage design and has passed rigorous industrial standard tests, which can suit for the industrial scene environment with harsh requirements for EMC. It can be widely used in smart grid, railway transportation, smart city, safe city, new energy, intelligent manufacturing and other industrial fields.


Dimension

Unit:mm


- ECU100-1T1F




- ECU100-2T1F




- ECU100-1GT1GF



● ECU100-2GT1GF



● ECU100-1GT2GS



Specification

Standard & Protocol

IEEE 802.3 for 10Base-T
 IEEE 802.3u for 100Base-TX and 100Base-FX
 IEEE 802.3z for 1000Base-X
 IEEE 802.3ab for 1000Base-T
 IEEE 802.3x for Flow Control

Interface

Copper port: 10/100Base-T(X) or 10/100/1000Base-T(X),
 RJ45, Automatic Flow Control, Full/half Duplex

Mode, MDI/MDI-X Autotuning
 1×9 fiber port: 100Base-FX or 1000Base-FX
 SFP slot: 1000Base-X, SFP slot

Indicator	STA Running Indicator, Port Indicator, LFP Indicator(1 copper port 1 fiber port product only)
Switch Property	<p>Transmission mode: store and forward Switch time delay: <10μs 100M Products:</p> <ul style="list-style-type: none"> ● MAC address: 2K ● Packet buffer size: 0.75M ● Backplane bandwidth: 0.8G <p>Gigabit Products:</p> <ul style="list-style-type: none"> ● MAC address: 8K ● Packet buffer size: 1M ● Backplane bandwidth: 14G
Power supply	Input voltage: 5VDC
Power consumption	<p>No-load: ≤1.5W@5VDC Full-load: ≤2.0W@5VDC</p>
Working environment	<p>Operating temperature: -40~75°C Storage temperature:-40~85°C Relative humidity: 5%~95% (no condensation)</p>
Physical Characteristic	<p>Installation: slide-in mounting Weight: ≤80g Dimension (W x H x D): 84.5mm×20.0mm×122.5mm</p>
Industrial Standard	<p>IEC 61000-4-2 (ESD, electrostatic discharge)</p> <ul style="list-style-type: none"> ● Air discharge: ±8kV ● Contact discharge: ±6kV <p>IEC 61000-4-4 (EFT, electrical fast transient pulses)</p> <ul style="list-style-type: none"> ● Power supply: ±2kV ● Signal: ±1kV <p>IEC 61000-4-5 (Surge)</p> <ul style="list-style-type: none"> ● Power supply: common mode±2kV, differential mode±1kV ● Signal: common mode ±2kV, differential mode ±1kV



Certification

CE, FCC, RoHS certification

Warranty

3 years

Ordering Information

Available Models	100M Copper Port	Gigabit Copper Port	100M Fiber Port	Gigabit Fiber Port	Gigabit SFP	Power supply
ECU100-1T1F-N	1	—	1	—	—	5VDC
ECU100-2T1F-N	2	—	1	—	—	
ECU100-1GT1GF-N	—	1	—	1	—	
ECU100-2GT1GF-N	—	2	—	1	—	
ECU100-1GT2GS-N	—	1	—	—	2	