

P1771Y-C6

17 PCAP Panel PC





Features

- 17" LCD, 1280*1024, resistive touch screen
- Intel® i5-8260U/1.6GHz quad cores 8-thread CPU
- 2*SODIMM DDR4 2400MHz, up to 64GB
- 1*HDMI
- 2*Intel I210 Gigabit Ethernet
- 6*RS232 (5*RS485/1*RS422), COM1~2 DB9, COM3-6 on 2*10Pin Phoenix connector
- 2*15Pin Phoenix connector, 4-in 4-out GPIO, power signal, 5V, GND
- 4*USB3.0, 2*USB2.0
- 9~36V voltage input
- Aluminum case, fanless design

Model No.	P1771Y-C6 V1.0(8260U)	
Chassis	Material/Structure	Aluminum case, fanless design
	Ingress Protection	IP65 (Front Panel)
	Dimension	L396*W333*H64mm
	Net Weight	5.12KG
	Installation	VESA mount / embedded
LCD Screen	Type	17" LCD
	Resolution	1280 * 1024
	Luminance	250 cd/m ²
Touch Screen	Type	Resistive
	Light Transmission	>82%
Mainboard	CPU	Onboard Intel® i5-8260U/1.60GHz quad cores 8-thread processor, TDP 15W
	Graphics	Integrated Intel® UHD Graphics 620
	Memory	2*DDR4 SODIMM RAM slot, 2400MHz, up to 64GB
IO Port	POWER	1*Power button, 1* One-key recovery, 1*AC LOSS (auto power ON/OFF)
	LED	1*Power LED, 1* HDD LED
	Display	1*HDMI
	LAN	2*Intel I210 Gigabit Ethernet, support Wake On LAN、 PXE
	USB	4*USB3.0, 2*USB2.0
	COM	6*RS232, COM1 DB9, COM2 DB9 RS232/485/422, COM3-6 RS232/485 on 2*10pin Phoenix connector, COM1-2 support pin9 charged function
	Phoenix Connector	2*15Pin (4-in 4-out GPIO, power signal, COM3~6 (RS232/485), 5V VCC and GND)
	DIP switch	10-digit dip switch for COM2~6 RS232/485/422 selection
	Audio	1*Line out, 1*MIC
	Power	1*DC aviation port, 1*2Pin Phoenix connector, support DC9~36V voltage input
Storage	SATA	1*2.5" SATA port
	M.2	1*M.2 SSD port, support Key-M, 2280, NVME PCIe4 SSD
	MSATA	1*MSATA SSD port
Expansion	M.2	1*M.2/WiFi, Key-E, 2230, support WiFi module
		1*M.2/5G, Key-B, 2242/52, support 5G module
OS Support	Windows	Windows 10
	Linux	Ubuntu
	Watch Dog	Support hardware reset function (L256, 0~255 seconds)
Power Supply	Power Type	External power supply
	Voltage Input	9V~36V
	Rate Consumption	60W~180W
Environment	Operating Temp.	-10°C ~ 50°C
	Storage Temp.	-20°C ~ 70°C
	Relative Humidity	5%-95% relative humidity, non-condensing
	Vibration	0.5g rms/5-500HZ/random/operating

P1771Y-C6 Dimension



Order Information

No.	Model	CPU	Memory	Motherboard	IO Board	GPIO	LAN	COM	HDMI	USB 2.0	USB 3.0	power
1	P1771Y-C6 V1.0(J6412)	J6412/2.00G	2*SODDDR4	P641	P1081-C6/P1071-LED	4-in 4-out	2	6	1	2	4	9~36V
2	P1771Y-C6 V1.0(8260U)	I5-8260U/1.6G	2*SODDDR4	P81	P1081-C6/P1071-LED	4-in 4-out	2	6	1	2	4	9~36V
3	P1771Y-C6 V1.0(7300U)	I5-7300U/2.6G	2*SODDDR4	P67	P1081-C6/P1071-LED	4-in 4-out	2	6	1	2	4	9~36V
4	P1771Y-C6 V1.0(1135G7)	I5-1135G7/2.4G	2*SODDDR4	P110	P1081-C6/P1071-LED	4-in 4-out	2	6	1	2	4	9~36V