


EPIC-E19_J126L VER:1.1



EPIC-E19_J126L VER:1.1 Front View



EPIC-E19_J126L VER:1.1 IO View



EPIC-E19_J126L VER:1.1 Lateral View

Model No.	EPIC-E19_J126L VER:1.1
Processor	Onboard Intel®J1900/2.0GHz quad-core processor, TDP 10W
Chipset	Intel® BayTrail SOC
RAM	1* SODIMM RAM slot, 1600/1333MHz DDR3L/1.35V, up to 8GB
Display	Integrated Intel®HD Graphics 1* VGA, 1*HDMI, 1* LVDS display port
LAN	2* RTL8111H Gigabit Ethernet, support Wake on LAN, PXE function
Storage	1* 7pin SATA2.0 hard disk port, transfer rate up to 3Gbps 1* MSATA SSD slot, transfer speed up to 3Gbps
Audio	Onboard ALC662 6-channel high definition audio controller, support MIC/Line-out. The power amplifier support 2Ω5W speaker
Expansion slot	1* Mini-PCIE slot, support WIF/4G module
Rear I/O Port	1* 12V DC_In 1* VGA 1* HDMI 2* USB3.0, 1* USB2.0 2* RJ45 Gigabit LAN port 1* Line-out (green)
Internal I/O Port	1* 4pin ATX power connector, support 12V power input output 1* JVGA, 1*12pin, same signal with DB15 VGA 1* LVDS port, 2*15pin, support dual channel 24BIT (LVDS can be changed to EDP port, optional) 1* Screen backlight power supply port, 1*6pin 4* USB2.0 port, 2*5pin 6* RS232 COM port, COM1 support pin9 charging function, COM2/COM3 support RS485 selectable 1*SATA power supply port, 1*4pin 1 Front audio port, 2*5pin 1* power amplifier port, 1*4pin 1* SIM slot 1* Front panel function button and LED indicator port, 2*5pin
Fan Connector	Fanless cooling, reserve 1*4pin CPU smart fan connector, 1*4pin system fan connector



GPIO Support 4-in 4-out GPIO
BIOS 64Mb Flash ROM
Watchdog Support hardware reset function (L256, 0~255 seconds)
Support OS Windows 10/Linux
Power Supply DC 12V
Operating Temperature -10°C ~ 60°C
Storage Temperature -20°C ~ 70°C
Working Humidity 5%-95% relative humidity, non-condensing
Dimension 148mm x 102mm

Order Information:

No	Model	Processor	Frequency	Memory	VGA	HDMI	LVDS	EDP	LAN	USB	COM	RS485/422	Power
1	EPIC-E19_J126L VER:1.1	J1900	2.0G	1* SODDR3L	1	1	2ch*24BIT	/	2*8111H	7	6	COM2	DC12V