


EPIC-E101_I726L VER:1.1



EPIC-E101_I526L VER1.1 Front View



EPIC-E101_I526L VER1.1 I/O View



EPIC-E101_I526L VER:1.1 Lateral View

Model No.	EPIC-E101_I726L VER:1.1(10710U)
Processor	Onboard Intel® 10 th Gen Core I7-10710U 1.1GHz6 cores 12-thread CPU, TDP15W Compatible with Intel® WhiskeyLake-U/CometLake-U/ CoffeeLake-U 8th/ 10th Celeron / Pentium/ I3/I5/I7 CPU
Chipset	SOC
Memory	1* DDR4 SODIMM RAM slot, 2666MH, up to 64GB
Display	Integrated Intel® UHD Graphics, support DirectX 12 OpenGL 4.5, 4K 1*VGA, 1* HDMI, 1*LVDS, support dual channel 24Bit
LAN	2* Intel WGI210AT Gigabit Ethernet, support Wake On LAN、 PXE
Storage	1* 7pin SATA3.0, transfer speed up to 6Gbps 1* MSATA SSD slot, transfer speed up to 6Gbps
Audio	Integrated ALC897 7.1+2 channel high fidelity audio controller, support Line_out、 amplifier, amplifier support 4 Ω /3W dual channel
Expansion Slot	1* Mini-PCIE slot, support WIFI/4G module
Rear I/O Port	1* DC 12V power input port 1* HDMI 1* VGA 2* USB3.0 1* USB2.0 2* RJ45 Gigabit LAN port 1* Line-out (green)
Internal I/O Port	1* 4pin power connector, support 12V power input output 1* JVGA, 1*12pin, same signal with DB15 1* LVDS, support dual channel 24BIT (can change to EDP, optional). 1* Screen backlight power supply port, 1*6pin 6*RS232 COM port, COM1 support pin9 charging function, COM2/3 RS232/485/422 4* USB2.0 port, 2*5pin 1* Front audio port, 2*5pin 1* Amplifier port, 1*4pin

1* SATA power supply port, 1*4pin

1* Front panel function button and LED indicator port, 2*5pin

Fan 1*4pin CPU smart fan connector, 1*3pin system fan connector

Connector

GPIO Support 4-in 4-out GPIO

BIOS 64Mb Flash ROM

Watchdog Support hardware reset function (L256, 0~255 seconds)

OS Support Windows7/Windows 10/Linux

Power Type DC 12V power supply

Operating Temp. -10℃~60℃

Storage Temp. -20℃~70℃

Relative Humidity 5%-95% relative humidity, non-condensing

Dimension 148mm x 102mm

Order Information:

No	Model	Processor	Frequency	Memory	VGA	HDMI	LVDS	EDP	LAN	USB	COM	RS485	Power
1	EPIC-E81_I526L VER:1.1(8260U)	I5-8260U	1.6G	1* SODDR4	1	1	2ch*24bit /	/	2*210AT	7	6	2	DC12V
2	EPIC-E100_I526L VER:1.1(10210U)	I5-10210U	1.6G	1* SODDR4	1	1	2ch*24bit /	/	2*210AT	7	6	2	DC12V
3	EPIC-E100_C326L VER:1.1(5205U)	5205U	1.9G	1* SODDR4	1	1	2ch*24bit /	/	2*210AT	7	6	2	DC12V
4	EPIC-E101_I726L VER:1.1(10710U)	I7-10710U	1.1G	1* SODDR4	1	1	2ch*24bit /	/	2*210AT	7	6	2	DC12V