


EPIC-E81_I526L VER:1.0 Specification



EPIC-E81_I526L VER1.0 Front View



EPIC-E81_I526L VER1.0 I/O View



EPIC-E81_I526L VER:1.0 Lateral View

Model No.	EPIC-E81_I526L VER:1.0(8260U)
Processor	Support Intel® 8 th Gen I5-8260U 1.6GHz quad core 8-Thread, TDP15W Compible Intel®WhiskeyLake-U/CometLake-U/CoffeeLake-U 8th/10th Celeron / Pentium/ I3/I5/I7 processor
Chipset	SOC
Memory	1* DDR4 SODIMM RAM slot, 2666MHz, up to 32GB
Display	Integrated Intel® UHD Graphics, support DirectX 12 OpenGL 4.5, 4K 1*VGA, 1* HDMI, 1*LVDS port, support dual channel 24Bit
LAN	2* Intel WGI210AT Gigabit Ethernet, support Wake On LAN、PXE
Storage	1* 7pin SATA3.0 slot, transfer speed up to 6Gbps 1* MSATA SSD slot, transfer speed up to 6Gbps
Audio	Onboard ALC897 7.1+2 channel high fidelity audio controller, support Line_out、Amplifier Amplifier support 4 Ω /3W dual channel
Expansion Slot	1* Mini-PCIE slot, support WiFi/4G module
Rear I/O Port	1* 12V DC_In jack 1* HDMI 1* VGA 2* USB3.0 1* USB2.0 2* RJ45 Gigabit LAN port 1* Line-out (green)
Internal I/O Port	1* 4pin power connector, support 12V power input output 1* JVGA port, 1*12pin, same signal with DB15 1* LVDS port, support dual channel 24BIT (1*EDP optional, same pin with LVDS) 1* Backlight power supply port (INVERTER1),1*6pin 6* RS232 COM port, COM1 pin9 support charged function, COM2/3 RS485/422 selectable 4* USB2.0, 2*5pin

- 1* Front audio port, 2*5pin
- 1* Amplifier port, 1*4pin
- 1* SATA power supply port, 1*4pin
- 1* Front panel power button and LED indicator port, 2*5pin
- Fan** 1*4pin CPU smart fan connector, 1*4pin system fan connector
- Connector**
- GPIO** Support 4-in 4-out GPIO
- BIOS** 64Mb Flash ROM
- Watchdog** Support hardware reset function (L256, 0~255 seconds)
- OS Support** Windows10/Windows 11/Linux
- Power Supply** DC 12V
- Operating Temp.** -10℃~60℃
- Storage Temp.** -20℃~70℃
- Relative Humidity** 5%-95% relative humidity, non-condensing
- Dimension** 148mm x 102mm

Order Information:

No	Model	Processor	Frequency	Memory	VGA	HDMI	LVDS	EDP	LAN	USB	COM	RS485	Power
1	EPIC-E81_I526L VER:1.0(8260U)	I5-8260U	1.6G	1* SODDDR4	1	1	2ch*24bit	/	2*210AT	7	6	2	DC12V
2	EPIC-E100_I526L VER:1.0(10210U)	I5-10210U	1.6G	1* SODDDR4	1	1	2ch*24bit	/	2*210AT	7	6	2	DC12V