



8 port PS2



8 port COMBO




8 port DVI

Features

- Meets EIA310c & IEC-3 specification
- 1U, Single slide rail, 17" or 19" LCD Keyboard drawer
- 8 port Combo, DVI or HDMI KVM switch
- Built-in 17" LCD monitor, 1280x 1024 resolution
- Option: 19", 1280x 1024 LCD monitor
- Industrial keyboard with touchpad
- Includes a key-locking mechanism to prevent unauthorized access
- Built-in rail self-locking device
- Tempered glass protect LCD screen

KVM switch

- 8 port Combo, DVI or HDMI KVM switch
- Support password protection and server name
- Support Windows, DOS, Netware, Unix, Linux, IMAC, Power MAC and Sun Micro systems with USB
- Hot plug- add or remove connected computer without powering off the KVM switch or computer
- No software required. Easy computer selection via Front push buttons, Hot Key, OSD manu
- Auto scan mode. Easy to monitor server operation



Specification

Model No	AMK808-CB	AMK808-VB
Construction	Heavy-duty steel	
Drawer design	1U, single slide rail LCD KB drawer for 19" cabinet	
Display	17", 1280x 1024 resolution with tempered glass Option: 19", 1280x 1024 with tempered glass	
Protection	Tempered glass protect LCD screen	
Physical security	Key locking mechanism	
KVM switch	8 port Combo KVM switch	8 port DVI-D KVM switch
Port connection	Daisy chain up to 8 levels to support up to 120 sets	
Port selection	8x Front push buttons, OSD Manu, Hotkey	
LED indication	Power LED indicates a computer is connecting Operation LED indicates the port has been selecting	
Keyboard	Industrial keyboard with touchpad Option KB: CH, FR, GR, IT, JP, KR, PT, RU, SP, UK, US	
Power supply	Built-in 60W, 90~264VAC, Operating temp.: -20~70°C	
Power consumption	3 watts stand-by, 25 watts in-use	
Dimension	442.4x 44x 590mm (Wx Hx D)	
Weight	13 kgs	
KVM cable	8x 1.8m USB KVM cable	8x 1.8m DVI/ USB cable

Environmental Factors

	Operating	Non-Operating
Temperature	0°C~50°C	-20°C~60°C
Relative Humidity	10%~90%	10%~95%
Approval	CE, FCC, RoHS	

Ordering Information

AMK808-17CBUS

1U, 17", 1280x 1024, 8-port Combo KVM, 8x 1.8m USB cables

AMK808-19CBUS

1U, 19", 1280x 1024, 8-port Combo KVM, 8x 1.8m USB cables

AMK808-17VBUS

1U, 17", 1280x 1024, 8-port DVI KVM, 8x 1.8m DVI/ USB cables

AMK808-19VBUS

1U, 19", 1280x 1024, 8-port DVI KVM, 8x 1.8m DVI/ USB cables

AMK808-17HBUS

1U, 17", 1280x 1024, 8-port HDMI KVM, 8x 1.8m HDMI/ USB cables

AMK808-19HBUS

1U, 19", 1280x 1024, 8-port HDMI KVM, 8x 1.8m HDMI/ USB cables

Option:

80W, 24~48VDC power supply

±48VDC power supply