

CV-119/M1001

19" TFT SXGA 5:4 Monitor with Touch (Projected Capacitive / Resistive 5-wire), 1x USB, 1x COM, 1x VGA, 1x DVI-D and 1x DisplayPort



Key Features

- 19" TFT SXGA 5:4 LCD with Resistive 5-wire / Projected Capacitive Touch
- Designed with Aluminum Die-Cast Front Frame
- 1x USB, 1x COM, 1x VGA, 1x DVI-D, 1x DisplayPort, 1x Audio
- IP 65 Compliant Front Panel
- Support Panel / Wall / VESA Mounting
- Convertible Display System (CDS) Supported
- Built-in Two 5W Internal Speakers

»» Overview

The 19" touch monitor with resistive 5-wire / projected capacitive touch screen offers resolution up to 1280x1024 (SXGA) and 350 nits brightness. CV-119/M1001 features flat surface and IP65 dust/waterproof front panel. In addition, designed with aluminum die-cast front frame, it is rugged and reliable for industrial environment. CV-119/M1001 supports Convertible Display System (CDS) which allows to configure, upgrade and maintain your touch monitor easily.

CV-119/M1001 supports both digital and analog signal input via three types of display interface: VGA, DVI-D and DisplayPort. Touch screen can be connected with USB or COM port. It has OSD function for adjusting the viewing options of display. With support to wide range power input from 9~48VDC, CV-119/M1001 is designed as an ideal solution for industrial application.

»» Specifications

Display

- LCD Size: 19" (5:4)
- Max. Resolution: 1280 x 1024
- Brightness (cd/m²): 350
- Contrast Ratio: 1000 : 1
- LCD Color: 16.7M
- Pixel Pitch (mm): 0.294 (H) x 0.294 (V)
- Viewing Angle (H-V): 170 / 160
- Backlight MTBF: 50000 hrs (LED Backlight)

Touch

- Resistive 5-wire Touch for CV-119R/M1001 Only
- Projected Capacitive Touch for CV-119C/M1001 Only

I/O Ports

- 1x VGA
 - 1x DVI-D
 - 1x DisplayPort
 - 1x Audio Input
 - 1x USB 2.0
 - 1x COM Port (Resistive Touch Only)
- (USB & COM Port are reserved for the connection to enable touch usage only)

Other Features

- Audio: AMP 5W + 5W (Internal Speaker)
- OSD Function: LCD On/Off, Auto, Menu, Up and Down
- Multi-language OSD Function

Power

- 1x 3-pin Terminal Block Connector with Power Input 9-48VDC
- 1x Optional AC/DC 12V/5A, 60W Power Adapter

Environment

- Operating Temperature: Ambient with air flow: 0°C to 50°C (with Industrial Grade Peripherals)
- Storage Temperature: -20°C to 60°C
- Relative humidity: 80% RH @ 50°C (Non-Condensing)
- IP Level: IP 65 Compliant Front Panel


Physical

- Dimension (WxHxD, mm): 510 X 389.3 X 73 mm
- Weight: 8.08 kg
- Construction Front Panel: Die-Casting Flat Surface
- Mounting: Panel / Wall / VESA Mounting


Certification

- CE
- FCC Class A

»» External I/O Mechanical Layout



»» Dimensions



>>> Ordering Information

Available Models

| Model No. | Product Description |
|----------------------|---|
| CV-119R/M1001 | 19" TFT SXGA 5:4 Monitor with Resistive 5-wire Touch , 1x USB, 1x COM, 1x VGA, 1x DVI-D and 1x DisplayPort |
| CV-119C/M1001 | 19" TFT SXGA 5:4 Monitor with Projected Capacitive Touch , 1x USB, 1x COM, 1x VGA, 1x DVI-D and 1x DisplayPort |

Package Checklist

CV-119/M1001

- CV-119/M1001 Touch Monitor x 1
- Panel Mounting Kit x 1
- Utility DVD Driver x 1
- Power Terminal Block Connector x 1
- USB Cable x 1
- VGA Cable x 1
- Screw Pack x 1

Optional Accessories

| Model No. | Description |
|--------------|---|
| GSM60A12-CIN | Adapter AC/DC 12V 5A 60W with 3pin Terminal Block Plug 5.0mm Pitch, GSM60A12-P1J |
| DVI-D Cable | DVI-D male to DVI-D male Cable 1.8M |
| SL2-SL3 | US 2 heads power cord, US B type to IEC C13, SVT 18AWG/3C Black 1.8M SL-2+SL-3 |
| SL6-SL3 | EU 2 heads power cord, EU G type to IEC C13, H05VV-F 0.75mm2/3G Black 1.8M SL-6+SL-3 |
| QP026-SL3 | UK 2 heads power cord, UK I type to IEC C13 ,H05VV-F 0.75mm2/3G Black 1.8M QP026+SL-3 |