

SYSG7010 Temperature & Humidity Sensor



Support support@exagate.com





Operational Properties

Power Supply Voltage	4,5 - 12 VDC
Power Consumption	0,005 - 0,007 A typical 0,006 A 0,0525 - 0,10 W typical 0,072 W
Operational Temperature Range	-25 +70 ₀C
Operational Humidity Range	0 - 85 % Rhv
Storage Temperature Range	-40 +85 °C
Storage Humidity Range	0 - 90 % Rh

Physical Properties

Dimensions (H x W x D)	56x44x25 mm 2.20x1.73x0.98 inch	
Color	Black	
Weight	60 (+/- 5%) grams	

Technical Properties

Temperature Measurement Range	-25 +70 ₀C			
Temperature Measurement Tolerance	+/- 0,2 _° C			
Temperature Measurement Resolution	0,1 oC			
Humidity Measurement Range	0 - 90 % Rh			
Humidity Measurement Tolerance	%0,5 Rh			
Humidity Measurement Resolution	%0,1 Rh			
Maximum Distance from Main Unit	200 m			
External Device Input	NO			
Power Over ExaBus Port	YES			
Power Over External Device	NO			







	PRODUCT SKU #	BARCODE #	P/N		DESCRIPTION	
	SYSG7010	8697270920521	7270SE21012		Temperature & Humidity Sensor	
Supp	Supported Units			SYSG4	001,SYSG7001	

LIMITED PRODUCT WARRANTY

All Exagate products are covered with 2 years limited guarantee from the date of original purchase. (Warranty duration may change depending on your country) Your sales or delivery receipt, showing the date of purchase of product is your proof of purchase. Exagate is obliged to repair or replace the defective hardware (or any part of it's) with no charge to owner.

Conditions Void of Warranty

- Damages on unit, cable or screen.
- Defections due to electrical wiring and/or city network.
- Interference to unit by non-authorized staff.
- Any problems caused by act of nature.
- Misusage of unit stated by the user manual.
- Removal or destruction of serial number, warranty labels.
- Any kind of modifications on unit.



